

CANAL SEAL

FOR IMPROVED MANAGEMENT OF IRRIGATION WATER. WHEN USED ACCORDING TO DIRECTIONS, CANAL SEAL HAS SHOWN TO REDUCE WATER LOSS IN CANALS DUE TO LEAKAGE AND SEAPAGE.

COMPOSITION

25% Liquid anionic polyacrylamide

All ingredients are exempt from the requirements or a tolerance as specified in 40 CFR 180.1001,c.

CAUTION:
KEEP OUT OF REACH OF CHILDREN
Read entire label for additional precautions.

NON-PLANT FOOD PRODUCT

MAY BE HARMFUL IF SWALLOWED. Avoid contact with eyes. Flush eyes with large quantities of water. **DO NOT RUB.** Contact Physician.

General Information

CANAL SEAL is a proprietary polymer mixture of polyacrylamide when used according to directions may significantly reduce water loss in canals due to leakage and seepage. CANAL SEAL flocculates suspended soil particles in irrigation water thus increasing their molecular weight, which promotes the heavy soil particles to drop to the bottom of the canal and seal existing cracks. Optimal application can be influenced by a variety of factors and therefore, it is recommended the user carefully observe the application to assure the desired results are achieved. CANAL SEAL is recommended for use at 4 - 6 gallons per treated acre and can be applied in a broadcast application either diluted with water or by itself.

To avoid product degradation and equipment corrosion, do not use iron, copper or aluminum containers or equipment.

Shake well before using this product.
Store at temperatures above 40 degrees F.

Exercise caution, spilled product creates very slippery conditions when wet. Contain the spill and collect without the use of water. Thoroughly collect spilled material by means of a suitable absorbent material and dispose of properly.

DIRECTIONS FOR USE

APPLICATION: CANAL SEAL can be applied in a broadcast application directly to the dry canal 2-5 days prior to the first water flow. CANAL SEAL should be applied at a rate of 4 - 6 gallons per treated acre. To calculate treated acres multiply the canal width by lineal feet and divide by 43,560 (square feet per acre). CANAL SEAL can be applied broadcast as is or diluted with water depending upon application equipment. **To prevent plugging, remove all screens prior to application.** For applications not diluted with water, clear sprayer, pump, and lines thoroughly with crop oil to remove any water and/or product residues. For applications diluted into water,

fill sprayer with appropriate volume of water and slowly add CANAL SEAL while maintaining agitation. For best results, it is recommended to use 1 gallon of CANAL SEAL per 30 gallons of water, (additional water volumes may be necessary to accommodate various types of application equipment). Do not attempt to mix more than 1 gallon of CANAL SEAL with less than 30 gallons of water as the material may become too thick to spray.

PRECAUTIONARY STATEMENTS

BEFORE USING THIS PRODUCT, READ ALL PRECAUTIONS, DIRECTIONS FOR USE, CONDITIONS OF SALE-LIMITED WARRANTY AND LIMITATIONS OF LIABILITY AND REMEDIES. KEEP OUT OF REACH OF CHILDREN. **CAUTION: SPILLED MATERIAL CREATES EXTREMELY SLIPPERY CONDITIONS. IF SPILLED CONTAIN, ABSORB WITH A SUITABLE ABSORBENT, AND DISPOSE OF ACCORDING TO LOCAL REGULATIONS.**

WHAT TO DO IN CASE OF CONTACT

If on skin: remove contaminated clothing and wash skin with soap and water. Call a physician. If swallowed: do not induce vomiting. Immediately call a physician. If in eyes: flush eyes with clean water for 15 minutes. Immediately call a physician. If inhaled: Move to fresh air and call a physician if irritation develops or persists.

STORAGE AND DISPOSAL

Store in original container only. Keep container tightly closed, do not allow water to be introduced into the contents of this container. Do not store near heat or open flame. Avoid contact with strong oxidizing agents. **Do not allow product to freeze in cold weather conditions.**

CONTAINER DISPOSAL: Triple rinse (or equivalent) and add rinsate to spray tank, then offer for recycling or reconditioning, or puncture and dispose of according to state and local authorities. If burned, stay out of smoke.

For help in chemical emergencies involving spill, leak, fire or exposure to CANAL SEAL, call 1-818-899-4686.

2 1/2 GALLONS (9.464L)

Always read and follow label directions before buying or using this product. **PROVEN QUALITY.** CANAL SEAL must not be repackaged without written permission. Notice to Buyer: The statements contained herein, including all descriptions of products and methods, test results, and suggestions are provided for your consideration only as general information and are not to be construed to constitute any representation or warranty, express or implied. Users assume full responsibility for determining the appropriate application of any products, method, or suggestions and for adopting such precautions against damage to property or injury to person's area as necessary or advisable under the circumstances. No statement contained herein is to be construed to constitute the permission, recommendation or encouragement of any use or application that may infringe any patents now or hereafter in existence. **NO WARRANTY OF MERCHANTABILITY OR WARRANTY OF SUITABILITY OF FITNESS FOR A PARTICULAR PURPOSE IS MADE.** No warranty, express or implied, is made except as may be provided in the Sales Contract or Invoice applicable to the goods in question.180402

Formulated Exclusively For:
American Soil Technologies, Inc.
12224 Montague Street
Pacoima, CA 91331
818-899-4686